



ISOTECH

Your Engineering Partner

Version 0.17



KTM Series Electrical Isolator


IP66 Isolator

ISOTECH with more than twenty years' experience in manufacturing for Load Break Switch (Isolator), ISOTECH covers from 16A to 200A. ISOTECH Load Break Switches offer maximum protection to both installation and the user with high IP rating. Our Isolators are manufacture and tested according to IEC60947-3 to ensure high quality of products which is fully adapted to harsh operating environments.

ISOTECH is the main solution provider for the global industries. Our clients include Food Processing Industry, Air Condition Industry, Heavy Industry and Power Distribution Industry. Work safety is always a top priority with **ISOTECH** isolators for service personnel can depend on reliable disconnection



KTM Series Features

- Design according to IEC60947-3
- Protection up to IP66
- Pad lockable 
- **With** interlocking system
- Interlock with defeat mechanism, KTM363B to KTM3200
- Sealing feature for Extra safety
- Premium moulding materials with excellent chemically resistance
- Good UV resistance
- Made in Malaysia



Rated Voltage Ue	Rated Current Ie	2 Pole Part No.	3 Pole + N Part No.	Max. Cable	Enclosure Size W x D x H (mm)
500V	16A	KTM216	KTM316	16mm ²	116 x 137 x 157
500V	25A	KTM225	KTM325	16mm ²	116 x 137 x 157
660V	40A	KTM240	KTM340	16mm ²	116 x 137 x 157
660V	63A	KTM263	KTM363	35mm ²	116 x 137 x 157
660V	63A	N/A	KTM363B	35mm ²	175 x 123 x 214
660V	75A	N/A	KTM375	35mm ²	175 x 123 x 214
660V	100A	N/A	KTM3100	35mm ²	175 x 123 x 214
660V	100A	N/A	KTM3100B	95mm ²	175 x 123 x 214
660V	125A	N/A	KTM3125	95mm ²	175 x 123 x 214
660V	160A	N/A	KTM3160	95mm ²	175 x 123 x 214
660V	200A	N/A	KTM3200	95mm ²	175 x 123 x 214