

Version 1.16



KTM 96 Series Electrical Isolator

IP65 Isolator

ISOTECH with more than twenty years' experience in manufacturing for Load Break Switch (Isolator), ISOTECH covers from 16A to 200A. ISOTECH Load Break Switches offer maximum protection to both installation and the user with high IP rating. Our Isolators are manufacture and tested according to IEC60947-3 to ensure high quality of products which is fully adapted to harsh operating environments.





ISOTECH is the main solution provider for the global industries. Our clients include Food Processing Industry, Air Condition Industry, Heavy Industry and Power Distribution Industry. Work safety is always a top priority with **ISOTECH** isolators for service personnel can depend on reliable disconnection.



KTM 96 Series Features

- Design according to IEC60947-3
- Captive Combination Head Screws for you choice of Screwdriver
- Large 16-95mm² Cable Conductor Terminals
- Steel plated terminals screws will never break
- Large padlocking capacity suit industry up to 12mm padlock
- With interlocking system
- Premium moulding materials with chemically resistance
- Made in Malaysia





Rated Voltage Ue	Rated Current le	2 Pole Part No.	3 Pole + N Part No.	Max. Cable	Enclosure Size W x D x H (mm)
500V	16A	KTM216-96	KTM316-96	16mm²	107 x 123 x 138
500V	25A	KTM225-96	KTM325-96	16mm²	107 x 123 x 138
660V	40A	KTM240-96	KTM340-96	16mm²	107 x 123 x 138
660V	63A	KTM263-96	KTM363-96	35mm ²	107 x 123 x 138
660V	63A	N/A	KTM363B-96	35mm²	175 x 123 x 214
660V	75A	N/A	KTM375-96	35mm²	175 x 123 x 214
660V	100A	N/A	KTM3100-96	35mm²	175 x 123 x 214
660V	100A	N/A	KTM3100B-96	95mm²	175 x 123 x 214
660V	125A	N/A	KTM3125-96	95mm²	175 x 123 x 214
660V	160A	N/A	KTM3160-96	95mm²	175 x 123 x 214
660V	200A	N/A	KTM3200-96	95mm²	175 x 123 x 214